




TECHNICAL SPECIFICATIONS


|                                  |                            |                              |                                  |
|----------------------------------|----------------------------|------------------------------|----------------------------------|
| Product name                     | GZHW 18XSPL-D1             | Gasket                       | Foam                             |
| Product type                     | Subwoofer chassis          | Terminal                     | Black chrome push terminal       |
| Diameter                         | 464 mm / 18.27"            | Power handling               | 4000 W SPL Power                 |
| Mounting diameter                | 425 mm / 16.73"            | Impedance                    | 2 x 1 Ohm                        |
| Mounting depth                   | 255 mm / 10.04"            | Re                           | 1.75 Ohm                         |
| Magnet dimension                 | 3 x 220x 20 mm             | Res                          | 28.3 Ohm                         |
| Total weight                     | 21.5 KG                    | FS                           | 34.3 Hz                          |
| Voice coil diameter              | 75 mm / 3" Round Wire      | Qms                          | 6.553                            |
| Voice coil winding height        | 45 mm / 1.77"              | Qes                          | 0.404                            |
| Voice coil wire material         | Copper                     | Qts                          | 0.381                            |
| Voice coil former material       | Aluminum                   | Rms                          | 19.982 kg/s                      |
| Top plate height                 | 13 mm / 0.51"              | Cms                          | 0.035 mm/N                       |
| Linear excursion (one direction) | 16 mm / 0.63"              | Mms                          | 606.79 gr                        |
| Effective Xmax                   | 45 mm / 1.77"              | BL                           | 23.778 N/A                       |
| Top Plate and T-Yoke color       | Black machined             | SPL (1w/1m)                  | 92 dB                            |
| Basket material                  | Aluminum Cast              | VAS                          | 75.21 L / 2.66 cu.ft             |
| Basket color                     | Yellow                     | Le                           | 2.37 mH                          |
| Spider                           | 2x Progressive Polycot     | Recommended freq. response   | 35 – 100 Hz                      |
| Surround                         | High Roll Sandwich Foam    | Recommended amplifier power  | 2000 – 4000 WRMS @2Ohm (0,5 Ohm) |
| Cone                             | Reinforced paper           | Sound Quality                | ⊕⊕⊕⊕⊕ (max. ⊕⊕⊕⊕⊕⊕⊕)             |
| Dustcap                          | IMPP konvex / with 3D Logo | SPL Competition              | ⊕⊕⊕⊕⊕ (max. ⊕⊕⊕⊕⊕⊕⊕)             |
| Magnetcover                      | PVC                        | Low bass performance 20-50Hz | ⊕⊕⊕⊕⊕⊕ (max. ⊕⊕⊕⊕⊕⊕⊕)            |
|                                  |                            | Mid bass performance 50-80Hz | ⊕⊕⊕⊕⊕ (max. ⊕⊕⊕⊕⊕⊕⊕)             |



|   |                 |
|---|-----------------|
| A | 464 mm / 18.27" |
| B | 425 mm / 16.73" |
| C | 255 mm / 10.04" |
| D | 225 mm / 8.86"  |
| E | 11.5 mm / 0.45" |



## BOX RECOMMENDATION




### Big size vented box

V: 140 L / 4.94 cu.ft

D: 200 mm / 8"

L: \*300 mm / 12"

No damping




### Medium size sealed box

30 – 60 L / 1.06 – 2.12 cu.ft

Qtc 0.71 – 0.57

40 - 60% polyester wool



### Medium size bandpassbox

V1: 50 L / 1.77 cu.ft

V2: 80 L / 2.82 cu.ft

D: 200 mm / 8"

L: \*280 mm / 11.02"

20% polyester wool in V1

No damping in V2

Die hier aufgeführten Gehäusevorschläge sind nur einige, der möglichen Varianten.


Bitte beachten Sie zudem, dass die finale Abstimmung, speziell die Port Längen je nach Fahrzeug und eigenem Geschmack variiert werden sollte.

*Above-mentioned enclosure recommendations are just a few possible variations.*

*Please note that you should find the perfect tuning, especially port length, based on your car and own taste.*



## BOX RECOMMENDATION



| Curve | Type               | Volume                                         | F3/ Qtc           |
|-------|--------------------|------------------------------------------------|-------------------|
| Red   | Vented             | 140 L / 4.94 cu.ft                             | 32 Hz             |
| Black | Sealed             | 30 L / 1.06 cu.ft                              | 63 Hz / 0.71      |
| Blue  | Sealed             | 60 L / 2.12 cu.ft                              | 66 Hz / 0.57      |
| Green | Bandpass 4th order | V1: 50 L / 1.77 cu.ft<br>V2: 80 L / 2.82 cu.ft | Centerfreq. 52 Hz |

Die hier aufgeführten Gehäusevorschläge sind nur einige, der möglichen Varianten.

Bitte beachten Sie zudem, dass die finale Abstimmung, speziell die Port Längen je nach Fahrzeug und eigenem Geschmack variiert werden sollte.

*Above-mentioned enclosure recommendations are just a few possible variations.*

*Please note that you should find the perfect tuning, especially port length, based on your car and own taste.*

