Zenith

versione/version:01/2024


BATTERIA "GEL" USO CICLO SENZA MANUTENZIONE
DEEP-CYCLE GEL MAINTENANCE FREE BATTERY


ZGEL1201105





CHARACTERISTIC / CARATTERISTICHE		
Volt		12V
Capacity / Capacità	20h	135Ah
	5h	110Ah
	3h	100Ah
	2h	95Ah
Capacity affected by Temperature / Effetti delle temperature sulla capacità	40°C	110%
	25°C	100%
	0°C	70%
Capacity affected by Temperature / Effetti della temperatura sui cicli di vita attesi	40°C	60%
	25°C	100%
	0°C	120%
Self-Discharge 25°C Capacity / Autoscarica a 25°C	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge cycle / Ciclo di carica	IU + h	"In" max. 42Amp; "V1" 2.40V/cell
	IUIa	"In" max. 42Amp; "V1" 14.1Volt; "If" 2Amp.

CHARACTERISTIC / CARATTERISTICHE		
Battery dimensions / Dimensioni batteria		
L/L	W/P	MAX - H/A
341	173	281
Box Dimensions / Dimensioni scatola		
L/L	W/P	H/A
-	-	-
USA Group		DIN
Weight / Peso		41,3 Kg
Terminal / Terminali		M8
Case / Contenitore		ABS
Pallet Qt		24









This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact U.B.S. UNION BATTERY SERVICE for the latest information.

Le informazioni contenute in questa scheda tecnica sono solo descrittive e indicative, non sono una garanzia. U.B.S. UNION BATTERY SERVICE si riserva il diritto di aggiornarle/modificarle senza preavviso.

Zenith


versione/version:01/2024

BATTERIA "GEL" USO CICLO SENZA MANUTENZIONE
DEEP-CYCLE GEL MAINTENANCE FREE BATTERY

ZGEL1201105




Charge cycles (25°C, discharge 5h)



D.O.D. (Deep Of Discharge)

Charge cycle for sealed batteries (GEL/AGM): IU + holding




In	=	PROGRAMMED CAPACITY/10
V0	=	1,90 V/CELL
V1	=	PROGRAMMED VALUE
V2	=	2.10 V/CELL
V3	=	2.30 V/CELL
T0	=	MAX. 1 HR
T1	=	MAX. 12 HRS
T2	=	T1 (MIN. 2-MAX. 5 HRS)
T3	=	UNLIMITED

"IUIa" charge cycle is always reccomended in case of more than 2 batteries in series
Ciclo di carica "IUIa" è sempre necessario qualora ci siano più di 2 batterie collegate in serie.

IUIa charge cycle

Only available for single-phase chargers



In	=	PROGRAMMED VALUE (CHARGE I)
If	=	PROGRAMMED VALUE (FINAL I)
V0	=	1,90 V/CELL
V1	=	PROGRAMMED VALUE (THRESHOLD V)
V2	=	PROGRAMMED VALUE (LOCK V)
V3	=	2.10 V/CELL
V4	=	2.30 V/CELL
T0	=	MAX. 1 HR
T1	=	MAX. 12 HRS
T2	=	MAX. T1+6 HRS OR I = IF
T3	=	MAX. 4 HRS
T4	=	UNLIMITED
T5	=	MAX. 6 HRS

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact U.B.S. UNION BATTERY SERVICE for the latest information.

Le informazioni contenute in questa scheda tecnica sono solo descrittive e indicative, non sono una garanzia. U.B.S. UNION BATTERY SERVICE si riserva il diritto di aggiornarle/modificarle senza preavviso.