







Tabella specifiche subwoofer

		Potenza massima (Watt)	Potenza massima RMS (Watt)	Impedenza (Ω)	Sensibilità (dB, 1 W/1m)	Risposta in frequenza (Hz)	Profondità di montaggio woofer (mm)	Diametro di taglio (mm)	Amplificatore consigliato (Mono)
	SWX-1243D	3000	1000	4 + 4	86	20-500	221	277	PDX-1.1000
	SWX-1043D	3000	1000	4 + 4	83	22-500	221	231	PDX-1.1000
	SWR-1542D	2000	750	4 + 4	87	22-500	234	349	PDX-1.1000
	SWR-1522D	2000	750	2 + 2	87	22-500	234	349	PDX-1.1000
	SWR-1242D	1500	500	4 + 4	85	24-500	196	275	PDX-1.600
	SWR-1222D	1500	500	2 + 2	85	24-500	196	275	PDX-1.600
	SWR-1042D	1500	500	4 + 4	83	28-500	172	231	PDX-1.600
	SWR-1022D	1500	500	2 + 2	83	28-500	172	231	PDX-1.600
		SWS-1223D	900	300	2 + 2	86	26-1k	130	271
SWS-1243D		900	300	4 + 4	86	26-1k	130	271	MRP-M850
SWS-1023D		900	300	2 + 2	84	30-1k	110	227	MRP-M850
SWS-1043D		900	300	4 + 4	84	30-1k	110	227	MRP-M850
	SWE-1243E	800	250	4	90	28-1k	172	278	MRP-M650
	SWE-1043E	500	150	4	88	33-1k	139	235	MRP-M450
	SWE-843E	400	120	4	87	34-1,5k	111	183	MRP-M352