

COMP HI ENERGY

HT 28 180 watt



Technical Specifications

Component	Tweeter	
Size	mm	28 (1 ^{11/16})
Power Handling	W peak	180
	Hi-pass filtered 2.0 kHz @ 12 dB Oct.	
Impedance	Ω	4
Frequency response	Hz	1.2k ÷ 22k
Sensitivity	dB/SPL	93
Outer Ø	mm	48
Mounting Ø	mm	45
Total depth	mm	29
Mount. depth	mm	19
Magnet size	mm	27,9
Weight of one speaker	kg	0,07
Voice coil Ø	mm	28



- 1 Tetolon® soft dome tweeter.
- 2 28mm ø, ferrofluid-cooled mobile voice coil.
- 3 High energy Neodymium magnet.
- 4 Rear acoustic chamber.
- 5 Revolving support and accessories for factory location and flush mounting.
- 6 Very flexible, high current input cable.



Electro-Acoustic Parameters

D	mm	28
Xmax	mm	-
Re	Ω	3,3
Fs	Hz	1000
Le	mH@1kHz	1,97
Le	mH@10kHz	0,05
Vas	l	-
Mms	g	0,3
Cms	mm/N	0,07
BL	T-m	2,20
Qts		1,04
Qes		1,38
Qms		4,20
Spl (1m/2,83V)	dB	93

