

# Performance P165V30



## 2-way kit

- 1" (25 mm) voice coil on Kapton® former
- High power handling**
- Polyglass cone
- Neutral sound without coloration**
- Semi-rigid dust cap
- Harmonic control**

- Butyl surround
- Excellent resistance**
- Engraved serial number
- Authenticity certificate**

- Aluminum chassis
- Rigid and non-magnetic**
- Diamond cutting finish
- For much style**



- Very low-resistance air core inductor
- Less efficiency loss, insensitive to parasite**
- Adjustable tweeter level
- Level adaptation according to its location**

- Voice-coil integrated cooling system
- Constant performance, optimum reliability**
- Streamlined decompressed magnet
- Perfect magnetic locking up, no ventilation noise**

- TNB inverted dome tweeter
- Details without directivity**
- Push-pull Neodymium dual magnet
- Very high tweeter linearity**
- Voice-coil on aluminum former
- Optimum thermal dissipation**
- Directivity part
- Broadens the soundstage**

- Polypropylene capacitor
- Natural treble reproduction**
- Smoked cap
- Much sobriety**
- Golden binding post terminals
- Insured link reliability**

## IT MAKES THE DIFFERENCE

- Lively reproduction
- High sensitivity
- 30 years of Focal know-how
- Special Edition model

## TECHNICAL CHARACTERISTICS

Woofers : 165 mm (6 1/2")  
Voice-coil : 25 mm (1")  
Magnet : 85 mm (3 1/3")  
TNB inverted dome

Separate crossover : 6/12 or 12/18 dB/oct (3.7kHz or 5kHz)  
Adjustable tweeter level : 0 – 3 dB/oct  
Max. power : 160W  
Nom. power : 80W

Sensitivity (2,8 V/1m) : 92 dB  
Frequency response : 55Hz – 28kHz  
Accessories : Grilles supplied