

Performance P130V15



2-way kit

- Butyl surround
- Promoting long life**
- Paint DIN basket 20% glass fiber filled ABS material
- Easy mounting, strong rigid basket**

- Polyglass cone
- Neutral sound without coloration**
- Acoustically transparent dust cap
- Better reproduction of mid frequencies**
- 1" [25mm] Kapton®, voice-coil former
- High power handling**
- Voice-coil cooling system
- Reliability, better sound quality**

- 6/12dB/oct. crossover
- Optimized woofer and tweeter integration**
- Adjustable tweeter level
- For a better adaptation of level/ placement in vehicle**
- Polypropylene capacitor
- Natural reproduction of high frequencies**



- Aluminum/magnesium inverted dome tweeter
- Optimized match between Polyglass woofer non directive**
- Double push-pull Neodymium magnet
- Very linear tweeter**
- Aluminum voice-coil former
- Excellent heat dissipation characteristics**

ADVANTAGES

- Outstanding musicality
- All Focal technologies

TECHNICAL CHARACTERISTICS

Woofer: 5 ¹/₈" [130mm]
Voice-coil: 1" [25mm]
Magnet: 3 ⁵/₁₆" [85mm]
Tweeter: 1 ³/₄" [45mm]

Aluminum/magnesium inverted dome
Separate crossover: 2-way 6/12dB/oct. [4.5kHz]
Adjustable tweeter level: 0, -3, -6 dB/oct
Max. power: 120W
Nom. power: 60W

Sensitivity [2.83 V/1m]: 91dB
Frequency response: 75Hz – 28kHz
Accessories: supplied grilles