

# 165 KR

2-way K2 Power kit

- K2 composite sandwich cone

**Impact and details**

- Zamak chassis

**Strong, rigid and non-magnetic chassis**

- Butyl surround

**Excellent reliability**

- Engraved serial number

**Certificate of authenticity**

- Adjustable tweeter 3 levels per stage of 3dB

**Installation flexibility**

- Polypropylene capacitor

**Neutral reproduction of high frequencies**

- Multi-wire air core inductor

**Resistant to parasites, maximum dynamic**



- TNK inverted dome tweeter

**Smoothness and precision**

- Neodymium ring magnet

**Very high linearity and dynamism**

- Foam surround

**Extended frequency response**

## Technical characteristics :

165mm (6.5") Woofer

25mm (1") Voice coil

85mm (3.5") Magnet

TNK inverted dome tweeter

Separate crossover : 12/12dB/oct (3.8kHz)

Adjustable tweeter level: (0,-3,-6dB)

Max. power: 160W

Nom. power: 80W

Sensitivity (2,83V/1m): 91dB

Frequency response: 60Hz – 20kHz

Accessories: grilles supplied

## It makes the difference:

- Treble smoothness
- Dynamic and neutrality
- Precision of sound stage
- Tweeter sound level adjustment
- Excellent linearity of the two speakers
- High sensitivity



**FOCAL**  
the Spirit of Sound