

# 165 KRX2

## 2-way K2 Power kit

- K2 composite sandwich cone

### Impact and details

- Zamak chassis

### Rigid and non-magnetic

- Aluminum phase plug

### Better midrange directivity

- Butyl surround

### Excellent reliability

- Serial number engraved in the block

### Authenticity certificate

- 2 Ohm voice coil

### Sensitivity rise

- Inverted dome tweeter TN53K

### Smoothness and accuracy

- Neodymium ring magnet

### Very high linearity and dynamics

- Foam separate surround

### Extended frequency response

- Phase part

### Slight directivity

- Adjustable tweeter level per step of 3dB

### Installation flexibility

- Polypropylene capacitor

### Natural treble reproduction

- Air core inductor

### Resistant to parasites, maximum dynamics

- Super Tweeter

### Emphasizes the extreme treble



### Technical characteristics :

Woofer: 6 1/2" [165mm]

Voice coil: 1 9/16" [40mm]

Magnet: 3 15/16" [100mm]

TN53K tweeter

Inverted dome

Separate crossover: Full/12 12/18dB/oct [4.7kHz]

Adjustable tweeter level: (0, -3, -6dB)

Max. power: 200W

Nom. power: 100W

Sensitivity [2.83V/1m]: 93dB

Frequency response: 70Hz – 20kHz

Accessories: grilles supplied

### It makes the difference:

- 2 Ohm voice coil
- High sensitivity
- Tweeter sound level adjustment

