



## MAXIMO COAX SPECIFICATIONS

SPECIFICATIONS	MAXIMO COAX 4 "	MAXIMO COAX 5 1/4 "	MAXIMO COAX 6 1/2 "	MAXIMO COAX 6x9"
Nominal Impedance	4 Ohm	4 Ohm	4 Ohm	4 Ohm
Power Handling	45W	70W	80W	100W
Max. Transient Power Handling	100W	140W	160W	200W
Sensitivity (2.83V/1M)	87.5dB	89.5dB	91dB	92dB
Frequency Response	75-20,000Hz	55-20,000Hz	55-20,000Hz	45-20,000Hz
Crossover Point				
Voice Coil Diameter	Woofer: 25mm (1") Tweeter: 19mm (0.8")	25mm (1") 19mm (0.8")	25mm (1") 19mm (0.8")	25mm (1") 19mm (0.8")
Voice Coil Wire	Copper	Copper	Copper	Copper
Magnet System	Woofer: High grade ferrite magnet Tweeter: Neodymium	High grade ferrite magnet Neodymium	High grade ferrite magnet Neodymium	High grade ferrite magnet Neodymium
Mounting Depth	52mm(2.1")	56mm(2.2")	63mm (2.5")	81mm (3.24")

\* Morel operates a policy of continuous products design improvement, consequently specifications are subject to alteration without prior notice.