

	MIDRANGES		TWEETERS						
	CDM880	CDM600	SUPREMO PICCOLO	MT250	MT230	MT220	MT120	TEMPO	MAXIMO
Nominal Impedance (Ohm)	4	4	6	6	6	4	4	4	4
Power Handling (WRms)	100	100	220	130	130	110	80	80	80
Max Transient Power Handling W (10ms)	300	300	1000	350	350	300	250	250	230
Sensitivity (2.83V/1M) dB	91	92	93	93	93	90	90	90	90
Frequency Response Hz	450-6000	600-6000	1400-25000	1400-25000	1600-25000	1600-25000	1800-22000	1800-22000	2200-22000
FS Hz	390	480	900	1100	1200	1150	1150	1200	1100
Voice Coil Diameter mm (inch)	54 (2.125)	54 (2.125)	28 (1.125)	28 (1.125)	28 (1.125)	28 (1.125)	28 (1.125)	28 (1.125)	25 (1)
Voice Coil Former	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Voice Coil Wire	Hexatech™ aluminum	Hexatech™ aluminum	Hexatech™ aluminum	Hexatech™ aluminum	Hexatech™ aluminum	Hexatech™ aluminum	Copper	Copper	Copper
DC Resistance Ohm	3.5	3.5	5.2	5.2	5.2	3.7	3.7	3.4	3.2
Magnet System	Neodymium rear vented	Neodymium rear vented	Neodymium flat pancake design	Double Magnet Neodymium	Double Magnet Neodymium	Neodymium	Neodymium	Neodymium	Neodymium
Dome Type	Acuflex™ hand coated soft dome	Selected soft dome	Acuflex™ hand coated soft dome	Acuflex™ hand coated soft dome	Acuflex™ hand coated soft dome	Acuflex™ hand coated soft dome	Acuflex™ hand coated soft dome	Selected soft dome	Selected soft dome
Dome Material	Silk	Silk	Silk	Silk	Silk	Silk	Silk	Silk	Silk
Unit Diameter mm (inch)	88.00 (3.50)	88.00 (3.50)	67mm (2.6)	45.00 (1.8)	45.00 (1.8)	45.00 (1.8)	45.00 (1.8)	45.00 (1.8)	45.00 (1.8)
Mounting Depth mm (inch)	21.00 (0.83)	21.00 (0.83)	32.00 (1.25)	20.00 (0.80)	20 (0.80)	20.00 (0.80)	20.00 (0.80)	20.00 (0.80)	20.00 (0.80)
Mounting Cutout mm (inch)	75.50 (2.97)	75.50 (2.97)	55 (2.16)	50.00 (2.00)	50.00 (2.00)	50.00 (2.00)	50.00 (2.00)	50.00 (2.00)	50.00 (2.00)
Net Weight Kg(lb)	0.25 (0.55)	0.25 (0.55)	0.35 (0.77)	0.07 (0.15)	0.067 (0.134)	0.06 (0.13)	0.06 (0.13)	0.06 (0.13)	0.06 (0.13)