

Specifications

Model	TA2.160	TA2.400	TA4.280	TA4.480	TA4.720	TA5.1250	TA1.600D	TA1.1000D	TA1.2000D	TA1.3000D
RMS Power 4Ω	55w x 2	135w x 2	50w x 4	90w x 4	120w x 4	95x4,325x1	250w x 1	400w x 1	700w x 1	800w x 1
RMS Power 2Ω	80w x 2	200w x 2	70w x 4	120w x 4	180w x 4	125x4 + 500x1	375 x 1	700w x 1	1,300w x 1	1,400w x 1
RMS Power 4Ω Bridged	160w x 1	400w x 1	140w x 2	240w x 2	360w x 2	250x2 + 750x1	-	-	-	2,000 x 1 (1Ω)
RMS Power 1Ω	-	-	-	-	-	-	600w x 1	1,000w x 1	2,000w x 1	3,000 x 1 (.5Ω)
Damping Factor	73	161	141	107	153	187	113	145	137	131
Signal-to-Noise Ratio	101dB	105dB	108dB	104dB	103dB	101dB	89dB	82dB	86dB	93dB
Channel Separation	49dB	55dB	48dB	42dB	47dB	48dB	-	-	-	-
Variable High Pass (1 & 2)	10-500Hz	10-500Hz	50-4kHz	50-4kHz	50-4kHz	50-4kHz	-	-	-	-
Variable High Pass (3 & 4)	-	-	15-50Hz	15-500Hz	15-500Hz	15-500Hz	-	-	-	-
Variable Low Pass (1 & 2)	50-500Hz	50-500Hz	-	-	-	-	40-220Hz	40-220Hz	40-220Hz	40-220Hz
Variable Low Pass (3 & 4)	-	-	50-400Hz	50-400Hz	50-400Hz	50-400Hz	-	-	-	-
Variable Bass Boost 45Hz	0 - 12dB	0 - 12dB	0 - 12dB	0 - 12dB	0 - 12dB	0 - 12dB	0 - 12dB	0 - 12dB	0 - 12dB	0 - 12dB
Variable Subsonic Filter	-	-	-	-	-	-	15-50Hz	15-50Hz	15-50Hz	15-50Hz
Remote Gain Control	-	-	-	-	-	-	Included	Included	Included	Included
On-Board Fusing	1 x 25A	2 x 25A	2 x 20A	2 x 30A	2 x 40A	1 x 80A	2 x 30A	2 x 40A	5 x 35A	(external)
Dimension (8.25"x1.75")	8.50"	13.25"	12.00"	15.50"	17.00"	17.25"	10.50"	13.25"	18.00"	20.50"