



Normal Impedance: $4+4\Omega$
Power RMS: 150W
Voice Coil $\varnothing$: 65mm
Sensitivity: 88dB
Fs: 23Hz

Frame: Aluminium
Cone: Paper
Magnet: Ferrite
Surround: Rubber
Voice Coil bi-wire winding: Copper
Voice Coil support: Glass Fiber

SPECIFICATIONS

Fs: 22.9360	VAS: 136.6373
Fs Added Mass: 18.6896	dB SPL: 88.1271
Fs Known Vol: 0.0000	L 1kHz: 1.0974
Added Mass: 60.0000	L 10kHz: 0.5109
Known Vol: 0.0000	CAS: 9.785215E-0007
Diameter: 250.0000	RAS: 2004.1640
ZMax: 21.4547	MAS: 49.2078
ZMax Added Mass: 19.8609	RAT: 19544.8700
ZMax Known Vol: 0.0000	SD: 0.0491
Z F1F2: 6.8702	LCES: 37.7607
Re: 2.2000	CMES: 1275.1600
Rms: 4.8292	RES: 19.2547
Qms: 3.5383	MMD: 112.4142
Qes: 0.4043	RMT: 47.0947
Qts: 0.3628	ETA: 0.3915
Cms: 0.4061	Z Min: 2.7408
Mms: 118.5698	Z AVG: 14.0721
BL: 9.6428	



IMPEDANCE

