

ZRX15D2

**Dual Voice Coil
Subwoofer 38 cm**

Power Handling
1500 Watts RMS / 3000 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	76 mm
Voice Coil Winding Height		40 mm
Max. Linear Excursion	Xmax	+/- 12,5 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 22 mm
Cone Area	Sd	810 cm ²
Moving Mass	Mms	369 g
DC Resistance	Re	2 x 2 Ohms
Resonance Frequency	Fs	28,5 Hz
Mechanical Q-Factor	Qms	6,08
Electrical Q-Factor	Qes	0,39
Total Q-Factor	Qts	0,37
Equivalent Air Volume	VAS	77,7 L
VC Inductance	Le	2,7 mH
Flux Density	B/L	24,99 N/A
Efficiency 1W/1m	SPL	88 dB

Recommended Enclosure

Ported Box	
Vented Volume:	100 L
Port Diameter:	2 x 100 mm
Port Area:	160 cm ²
Port Length:	15 cm
Tuning Freq. (Fb):	42 Hz
-3 dB Rolloff (F3):	34 Hz

SPL

Recommended Enclosure

Ported Box	
Vented Volume:	76 L
Port Diameter:	2 x 100 mm
Port Area:	160 cm ²
Port Length:	44 cm
Tuning Freq. (Fb):	33 Hz
-3 dB Rolloff (F3):	29 Hz

Sound Quality

Mechanical Components

- Diecast Aluminium Basket
- Non-pressed Paper Cone
- Foam Surround
- Injected PP Dustcap
- Triple Polycot Spider
- Dual Magnet 2 x 90 oz (5.103 g)
- Magnet Size: Ø190 x 50 mm

Dimensions & Weight

External Diameter:	394 mm
Mounting Diameter:	352 mm
Mounting Depth:	201 mm
Shipping Weight:	17,4 kg

