

ZRX8D2

Power Handling
600 Watts RMS / 1200 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	64 mm
Voice Coil Winding Height		35 mm
Max. Linear Excursion	Xmax	+/- 12,5 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 18 mm
Cone Area	Sd	204 cm ²
Moving Mass	Mms	148,2 g
DC Resistance	Re	2 x 2 Ohms
Resonance Frequency	Fs	40,4 Hz
Mechanical Q-Factor	Qms	5,26
Electrical Q-Factor	Qes	0,47
Total Q-Factor	Qts	0,43
Equivalent Air Volume	VAS	6,1 L
VC Inductance	Le	2,4 mH
Flux Density	B/L	18,3 N/A
Efficiency 1W/1m	SPL	82 dB

Mechanical Components

- Diecast Aluminium Basket
- Non-pressed Paper Cone
- Foam Surround
- Injected PP Dustcap
- Dual Polycot Spider
- Dual Magnet 2 x 60 oz (3.402 g)
- Magnet Size: Ø156 x 50 mm



Dual Voice Coil
Subwoofer 20 cm

Recommended Enclosure

Ported Box	
Vented Volume:	25 L
Port Diameter:	100 mm
Port Area:	80 cm ²
Port Length:	39 cm
Tuning Freq. (Fb):	44 Hz
-3 dB Rolloff (F3):	36 Hz

SPL

Recommended Enclosure

Ported Box	
Vented Volume:	20 L
Port Diameter:	80 mm
Port Area:	50 cm ²
Port Length:	42 cm
Tuning Freq. (Fb):	39 Hz
-3 dB Rolloff (F3):	33 Hz

Sound Quality

Dimensions & Weight

External Diameter:	220 mm
Mounting Diameter:	184 mm
Mounting Depth:	144 mm
Shipping Weight:	9,2 kg