

**POWER FOR THE WAVES THE PURE MARINE CERTIFIED PRODUCT**

# HTX 8 M-FL-W

MARINE TOWER COAX FLAT WHITE

# HTX 8 M-FL-C

MARINE TOWER COAX FLAT BLACK



## TECHNICAL SPECIFICATIONS

<b>Component</b>	Two way coaxial	
<b>Size</b>		
Woofers	mm (in.)	200 (8)
Tweeter diaphragm	mm (in.)	36 (1.4)
<b>Voice Coil Ø</b>		
Woofers	mm (in.)	32 (1.26)
Tweeter	mm (in.)	20 (0.8)
<b>Power Handling</b>		
	W peak	200
	W continuous	100
<b>Impedance</b>	Ω	4
<b>Frequency Response</b>	Hz	45 ÷ 25k
<b>Woofers Magnet size D x d x h</b>	mm (in.)	90 x 40 x 20 (3.54 x 1.57 x 0.79)
<b>Tweeter Magnet size D x h</b>	mm (in.)	19,7 x 3 (0.78 x 0.12)
<b>Weight of one speaker</b>	kg (lb.)	5,4 (11.9)
<b>Woofers Magnet</b>	High density flux ferrite	
<b>Tweeter Magnet</b>	Neodymium	
<b>Cone</b>	Polypropylene with UV inhibitors	
<b>Dome</b>	PEI	
<b>Xmech</b>	mm (in.)	±8,5 (0.33)

## ELECTRO-ACOUSTIC PARAMETERS

<b>D</b>	mm	174
<b>Xmax</b>	mm	4,5
<b>Re</b>	Ω	3,4
<b>Fs</b>	Hz	51
<b>Le</b>	mH	0,46
<b>Vas</b>	l	26,1
<b>Mms</b>	g	30
<b>Cms</b>	mm/N	0,33
<b>BL</b>	T·m	6,33
<b>Qts</b>		0,78
<b>Qes</b>		0,82
<b>Qms</b>		14,7
<b>Spl</b>	dB	91

1. Hertz **Pure Marine Certified Product** stamp featuring the IP65 protection grade, ASTM-D4329 standards for UV resistance and ASTM-B117 for salt fog operability.
2. Equipped with dedicated 8" coaxial speaker featuring a long-throw 32 mm (1.26") voice coil woofer with polypropylene cone injected with UV inhibitors and 1.4" Neodymium magnet tweeter.
3. RGB led lighting creates sophisticated atmosphere, adding tons of class to your vessel. Front RGB lighting is included built-in the front grille, while rear RGB lighting is an add-on with the specifically developed HTX RGB LOGO.1 accessory (available both in black and white color).



HM RGB 1 BK - Optional



### HTX RGB W LOGO.1

OPTIONAL RGB LED LIGHTING REAR LOGO WHITE



### HTX RGB C LOGO.1

OPTIONAL RGB LED LIGHTING REAR LOGO BLACK

The optional rear Hertz led logo creates the same sophisticated atmosphere of front led, adding tons of class to your vessel.

<b>A</b>	225 mm	8.86 in.
<b>B</b>	288 mm	11.34 in.
<b>C</b>	231 mm	9.09 in.
<b>D</b>	6 mm	0.24 in.

