

ZXT10D2

**Dual Voice Coil
Subwoofer 25 cm**

**Power Handling
2500 Watts RMS / 5000 Watts Max.**

Technical Specifications

| | | |
|---------------------------|-------------|---------------------|
| Impedance | Zn | 2 x 2 Ohms |
| Voice Coil Diameter | Ø | 76 mm |
| Voice Coil Winding Height | | 57,5 mm |
| Max. Linear Excursion | Xmax | +/- 23 mm |
| Max. Mechanical Excursion | Xmax (Peak) | +/- 30 mm |
| Cone Area | Sd | 330 cm ² |
| Moving Mass | Mms | 282 g |
| DC Resistance | Re | 2 x 1,9 Ohms |
| Resonance Frequency | Fs | 46 Hz |
| Mechanical Q-Factor | Qms | 4,1 |
| Electrical Q-Factor | Qes | 0,61 |
| Total Q-Factor | Qts | 0,53 |
| Equivalent Air Volume | VAS | 6,2 L |
| VC Inductance | Le | 1,52 mH |
| Flux Density | B/L | 23,3 N/A |
| Efficiency 1W/1m | SPL | 83 dB |

Recommended Enclosure

| | |
|---------------------|--------------------|
| Ported Box | |
| Vented Volume: | 35 L |
| Port Diameter: | 100 mm |
| Port Area: | 80 cm ² |
| Port Length: | 24 cm |
| Tuning Freq. (Fb): | 45 Hz |
| -3 dB Rolloff (F3): | 36 Hz |

Mechanical Components

- Diecast Aluminium Basket
- Carbon Composite Cone
- Foam Surround
- Carbon Dustcap
- Triple Nomex Spider
- Triple Magnet 3 x 100 oz (8.505 g)
- Magnet Size: Ø220 x 60 mm
- BASV Voice Coil Former

Dimensions & Weight

| | |
|--------------------|---------|
| External Diameter: | 262 mm |
| Mounting Diameter: | 235 mm |
| Mounting Depth: | 198 mm |
| Shipping Weight: | 22,0 kg |

