


CAN123.00TH

Lavoce

12" COAXIAL

NEODYMIUM COMMON HF/LF MAGNET
ALUMINIUM BASKET DRIVER

- 3 INCH LF COPPER VOICE COIL- 3 INCH HF EDGEWOUND CCA VOICE COIL- 99,5 dB/SPL SENSITIVITY- 700 WATT PROGRAM POWER HANDLING- FEM OPTIMIZED COMMON MOTOR, PATENTED IIS PHASEPLUG AND DIAPHRAGM- 45 - 18000 Hz FREQUENCY RANGE- 60°x40° NOMINAL COVERAGE- COMPOSITE TITANIUM/POLYIMIDE HF DIAPHRAGM- DOUBLE ALUMINIUM DEMODULATING RINGS- COMPACT AND LIGHTWEIGHT DESIGN



GENERAL SPECIFICATIONS LF

Nominal Diameter	300 mm (12 in)
Nominal Impedance	8 ohm
Minimum Impedance	6.2 ohm
Program Power	700 W Program power is defined as 3 dB greater than AES Power.
AES Power Rating	350 W Tested in free air for two hours using a continuous: LF:band-limited pink noise signal as per AES 2-1984 Rev. 2003. HF:band-limited (1000-20000 Hz, 12dB/oct.) pink noise signal as per AES 2-1984 Rev. 2003.
Sensitivity	99.5 dB LF: From T/S parameters, measured with Klippel DA LPM module. HF: Measured on axis at 2.83V, 1m, SPL averaged in the frequency range 600 ÷ 18000 Hz.
Frequency Range	45 ÷ 3500 Hz
Voice Coil Diameter	75 mm (3 in)
Chassis Material	ALUMINIUM
Magnet Material	NEODYMIUM
Magnet Dimensions OD X ID X H	135 x 85 x 10 mm (5.31 x 3.35 x 0.39 in)
Coil Material	COPPER
Former Material	GLASS FIBER
Cone Material	WATER RESISTANT TREATED PAPER + WATER PROOF FRONT SIDE TREATMENT
Surround Material	POLYCOTTON
Flux Density	1.2 T
Xmax	6 mm (0.24 in) The Xmax is calculated as: (Hvc - Hg)/2+ Hg/4. Hvc is the voice coil height and Hg the gap height.
Xmech	10 mm (0.39 in) The Xmech is calculated as: (Hvc - Hg)/2 +(Hg-2). Hvc is the voice coil height and Hg the gap height.
Gap Height	8 mm (0.31 in)
Voice Coil Winding Height	16 mm (0.63 in)
Driver Displacement Volume	2.7 l (0.1 ft³)
Recommended Enclosure	54 l (1.91 ft³)

Recommended Tuning	66 Hz
Recommended Crossover	– High pass filter with slope 12dB/oct. or higher.

GENERAL SPECIFICATIONS HF


HF Exit	36 mm (1.4 in)
Nominal Impedance	8 ohm
Minimum Impedance	8 ohm
Program Power	160 W Program power is defined as 3 dB greater than AES Power.
AES Power Rating	80 W Tested in free air for two hours using a continuous: LF:band-limited pink noise signal as per AES 2-1984 Rev. 2003. HF:band-limited (1000-20000 Hz, 12dB/oct.) pink noise signal as per AES 2-1984 Rev. 2003.
Sensitivity	106 dB LF: From T/S parameters, measured with Klippel DA LPM module. HF: Measured on axis at 2.83V, 1m, SPL averaged in the frequency range 600 ÷ 18000 Hz.
Frequency Range	600 ÷ 18000 Hz
Voice Coil Diameter	75 mm (3 in)
Coil Material	EDGEWOUND CCA
Former Material	KAPTON
HF Dome Material	TITANIUM
Surround Material	POLYIMIDE
Flux Density	1.9 T
Recommended Crossover	1200 Hz High pass filter with slope 12dB/oct. or higher.

SMALL SIGNAL PARAMETERS LF

Thiele–Small parameters are measured after preconditioning: a) at 20°C– 22°C, 50% humidity for 2 hours; b) by Klippel LSI measurement.

DC Resistance (Re)	5.3 ohm
Diaphragm Area (Sd)	531 cm² (82.31 in²)
Resonance Frequency (Fs)	46 Hz
Moving Mass (Mms)	52.5 g (1.85 oz)
Compliance (Cms)	0.23 mm/N
Force Factor (BxL)	18.5 N/A
Mechanical Q-Factor (Qms)	4
Electrical Q Factor (Qes)	0.23
Total Q-Factor (Qts)	0.22
Equivalent Air Volume (Vas)	91 l (3.21 ft³)
Voice Coil Inductance (Le)	0.5 mH
Reference Efficiency (Eta 0)	3.6 %
Efficiency Bandwidth Product (EBP)	200 Hz

DIMENSIONS



SHIPPING INFORMATION

Net Weight	5 kg
Multipack Quantity	1
Multipack size W x D x H	343 mm x 343 mm x 225 mm (13.5 in x 13.5 in x 8.9 in)
Multipack Weight	6.1 kg (13.45 lb)

REPAIR KITS

LF Repair Kit	VRK07121
HF Repair Kit	VRK83141

All the specifications subject to change without notice.



WWW.LAVOCESPEAKERS.COM



Lavoce

sales@lavocespeakers.com sales.cn@lavocespeakers.com